


④ FLOOR PLAN
3/4" = 1'-0"



Level 1
0.00

③ SOUTH
3/4" = 1'-0"

This is a high-quality loudspeaker certified for EN54 voice alarm systems for fire detection and fire alarm systems for buildings.

CE marking according to the Construction Products Regulation EU N° 305/2011.

The performed type testing, the initial inspection of the manufacturing plant and the factory production control with continuous surveillance assessment and approval of the factory production control is done by a notified body.

All technical specifications, EASE-simulation-data and the DoP (Declaration of Performance) can be downloaded in the EN54 product section of our website www.ic-audio.com

Speaker Schedule-ic audio								
count	Manufacturer	Description	Model	Electrical Data	Ip rating	Weight	Part number	Frequency Range
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-50 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-25 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-13 VA	IP33	3,75	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-6 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-50 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-25 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-13 VA	IP33	3,75	20122648 & 20122647	63 - 20.100 Hz
1	ic audio GmbH Germany	2-Way-monitor speaker for Voice Alarm EN54	MS 50-165/T-EN54 black & MS 50-165/T-EN54 white	120 V/1-6 VA	IP33	1,75 kg	20122648 & 20122647	63 - 20.100 Hz