Boehringerstraße 14a
D-68307 Mannheim
Germany





2 CEILING PLAN
1" = 1'-0"



3 SOUTH
1" = 1'-0"

This is a high-quality loudspeaker certified for EN54 voice alarm systems for fire detection and fire alarm systems for buildings.

CE marking according to the Construction Products Regulation EU N° 305/2011.

The performed type testing, the initial inspection of the manufacturing plant and the factory production control with continuous surveillance assessment and approval of the factory production control is done by a notified body.

Speaker Schedule-WA 06-165_T-Metall - EN54

Count	Manufacturer	Description	Model	Ip rating	Weight	Part number	Frequency Range
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz
1	ic audio GmbH Germany	Vandal proof wall mounted speaker for Voice Alarm EN54	WA-06-165/T Metall-EN54	IP21	2,04 kg	20102198	170 - 18.500 Hz