

Tender Specification

DK-SF 10/T-PG MED

Weatherproof horn loudspeaker with high sound pressure, 10W, 100V, certified acc. to MED/1.44b

MED/1.44b certified loudspeaker with 100V transformer and 4 power tapplings; low-impedance operation (20 Ohm) also possible.

Impact-resistant and UV-resistant ABS housing acc. to UL94V0 in RAL 7035.

Integrated ceramic block and thermal fuse for additional operational safety.

IP66 protection class against environmental influences.

PG11 cable glands on the rear for quick, uncomplicated connection.

Includes U-shaped V4A universal bracket and V4A screws for flexible mounting.

Suitable for demanding environmental conditions in maritime applications.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	10/5/2,5/1,25 (20)
Low impedance matching (Ohm):	1000/2000/4000/8000
Dimensions (mm):	142x256
Weight (kg):	1,9
Colour:	RAL 7035
Frequency response IEC268-5 (-10dB) (Hz):	569-7.000
Frequency range (Hz):	370-13.600
Dispersion angle -6 dB, 500 Hz:	360° h/v
Dispersion angle -6 dB, 1 kHz:	360° h/v
Dispersion angle -6 dB, 2 kHz:	105° h/v
Dispersion angle -6 dB, 4 kHz:	50° h/v