

Tender Specification

DL-E 06-165/T-EN54W

Ceiling loudspeaker, 6W, 100V, certified acc. to EN 54-24

6W ceiling loudspeaker with 165mm wide-range chassis and 100V transformer with 3 power tapings.

Plastic-coated metal housing, extremely flat design with only 70mm installation depth and under 1kg weight.

Innovative air flow system for sound characteristics comparable to a conventional bass loudspeaker.

Moisture-impregnated speaker for additional operational reliability.

Connection via WAGO 221 screw terminal.

Quick installation via spring-loaded snap-fastener with short travel.

IP21 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	6/3/1,5
Low impedance matching (Ohm):	1667/3333/6667
Dimensions (mm):	200x94
Weight (kg):	0,93
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	300-19.300
Frequency range (Hz):	70-23.500
Sensitivity EN54-24, 1W/4m (dB):	78
Ceiling cut out (mm):	166
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	180° h/v
Dispersion angle -6 dB, 2 kHz:	135° h/v
Dispersion angle -6 dB, 4 kHz:	60° h/v