

Tender Specification

DL-SE 06-100/T-EN54

Ceiling loudspeaker, 6W, 100V, certified acc. to EN 54-24

Splash-proof design loudspeaker series, suitable for swimming pools, bathrooms and humid areas.
6W ceiling loudspeaker with 100mm wide-range chassis and 100V transformer with 3 power tapings.

Plastic-coated metal housing with perforated grille.

Moisture-impregnated speaker for additional operational reliability.

Connection via WAGO 221 screw terminal.

Quick installation via spring-loaded snap-fastener with short travel and protective caps on the spring ends.

ABS back box included in delivery.

IP54 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	6/3/1,5
Low impedance matching (Ohm):	1667/3333/6667
Dimensions (mm):	140x94
Weight (kg):	0,68
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	230-12.000
Frequency range (Hz):	220-14.000
SPL IEC268-5, 1W/1m (dB):	91
Sensitivity EN54-24, 1W/4m (dB):	68,5
Ceiling cut out (mm):	129
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	180° h/v
Dispersion angle -6 dB, 2 kHz:	180° h/v
Dispersion angle -6 dB, 4 kHz:	81° h/v