

Tender Specification

DL-SE 10-165/T plus-EN54

Ceiling loudspeaker, 10W, 100V, certified acc. to EN 54-24

10W ceiling loudspeaker with frameless design and 165mm wide-range driver, 100V transformer with 3 power tapings.

Plastic-coated metal housing with perforated grille in RAL 9016.

Moisture-impregnated loudspeaker chassis for additional operational reliability.

IP21 protection class.

Fast and convenient connection via WAGO 221 terminal block.

Mounting via spring snap fastener with short travel, protective caps on the spring ends minimise vibration; alternatively mountable via threaded rod.

Special finish in RAL or NCS colour available at extra cost.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	10/5/2,5
Low impedance matching (Ohm):	1000/2000/4000
Dimensions (mm):	220x108
Weight (kg):	1,33
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	105-17.000
Frequency range (Hz):	80-18.000
SPL IEC268-5, 1W/1m (dB):	97,0
Sensitivity EN54-24, 1W/4m (dB):	83,1
Ceiling cut out (mm):	188
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	163° h/v
Dispersion angle -6 dB, 2 kHz:	118° h/v
Dispersion angle -6 dB, 4 kHz:	68° h/v