

Tender Specification

DL-SE 20-200/T black-EN54

Ceiling loudspeaker, 20W, 100V, certified acc. to EN 54-24

Frameless design, inspired by modern LED lighting.

20W ceiling loudspeaker with 200mm wide-range chassis and 100V transformer with 3 power tapings.

Plastic-coated metal housing with perforated grille.

Moisture-impregnated speaker for additional operational reliability.

Also suitable for very thin ceilings.

Connection via WAGO 221 screw terminal.

Quick installation via spring-loaded snap-fastener with short travel and protective caps on the spring ends.

Back box included in delivery.

IP21 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	20/10/5
Low impedance matching (Ohm):	500/1000/2000
Dimensions (mm):	265x115
Weight (kg):	1,61
Colour:	RAL 9005
Frequency response IEC268-5 (-10dB) (Hz):	60-17.500
Frequency range (Hz):	100-20.000
SPL IEC268-5, 1W/1m (dB):	94,8
Sensitivity EN54-24, 1W/4m (dB):	85,2
Ceiling cut out (mm):	240
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	155° h/v
Dispersion angle -6 dB, 2 kHz:	100° h/v
Dispersion angle -6 dB, 4 kHz:	60° h/v