

Tender Specification

DL-S 15-100/T plus MED

Low-profile ceiling loudspeaker, 15W, 100V, certified acc. to MED/1.44b

Low-profile design, MED/1.44b certified, suitable for use in any ship environment.

Powerful 2-way bass-reflex system with 100mm polypropylene woofer and precise 25mm tweeter for excellent music reproduction.

Wide dispersion for even room coverage.

Screw terminal with IN-OUT for loop connections; power tapping via rotary switch.

Low-impedance operation possible.

Magnetic grille and screw mounting system for easy installation.

High-quality ABS housing.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	15/7,5/3,75 (8)
Low impedance matching (Ohm):	667/1333/2666
Dimensions (mm):	242x108
Weight (kg):	1,87
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	100-16.900
Frequency range (Hz):	90-17.000
Ceiling cut out (mm):	210
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	175° h/v
Dispersion angle -6 dB, 2 kHz:	170°/160° h/v
Dispersion angle -6 dB, 4 kHz:	100°/35° h/v