

# Tender Specification

## DL-S 30-130/T plus MED

### Low-profile ceiling loudspeaker, 30W, 100V, certified acc. to MED/1.44b

Low-profile design, MED/1.44b certified, suitable for use in any ship environment.

Powerful 2-way bass-reflex system with 130mm polypropylene woofer and precise 25mm tweeter for excellent music reproduction.

Wide dispersion for even room coverage.

Screw terminal with IN-OUT for loop connections; power tapping via rotary switch.

Low-impedance operation possible.

Magnetic grille and screw mounting system for easy installation.

High-quality ABS housing.

RoHS compliant.

#### Technical Data:

|                                           |                    |
|-------------------------------------------|--------------------|
| Rated power/rated noise power 100 V (W):  | 30/15/7,5/3,75 (8) |
| Low impedance matching (Ohm):             | 333/667/1333/2666  |
| Dimensions (mm):                          | 322x128            |
| Weight (kg):                              | 2,99               |
| Colour:                                   | RAL 9016           |
| Frequency response IEC268-5 (-10dB) (Hz): | 70-20.500          |
| Frequency range (Hz):                     | 60-21.000          |
| Ceiling cut out (mm):                     | 291                |
| Dispersion angle -6 dB, 500 Hz:           | 180° h/v           |
| Dispersion angle -6 dB, 1 kHz:            | 165° h/v           |
| Dispersion angle -6 dB, 2 kHz:            | 145°/170° h/v      |
| Dispersion angle -6 dB, 4 kHz:            | 75°/60° h/v        |