

Tender Specification

DL-S 60-165/T plus white-EN54

Ceiling loudspeaker, 60W, 100V, certified acc. to EN 54-24

60W ceiling loudspeaker with 2-way bass-reflex system, 165mm polypropylene woofer and 25mm tweeter.

Flat, low-profile design for unobtrusive installation.

ABS housing.

Connection via 6-pole screw terminal with IN-OUT for loop connections.

Power tapping via rotary switch, low-impedance operation possible.

Magnetic grille and screw mounting system for easy installation.

IP21 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	60/30/15/7,5 (8)
Low impedance matching (Ohm):	167/333/667/1333
Dimensions (mm):	322x128
Weight (kg):	3,01
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	63-21.000
Frequency range (Hz):	70-20.500
SPL IEC268-5, 1W/1m (dB):	91,3
Sensitivity EN54-24, 1W/4m (dB):	77,6
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	180° h/v
Dispersion angle -6 dB, 2 kHz:	105°/96° h/v
Dispersion angle -6 dB, 4 kHz:	57°/75° h/v