

Tender Specification

PRO 60-130/T plus black-EN54

Weatherproof coaxial loudspeaker, 60W, 100V, certified acc. to EN 54-24

Weatherproof coaxial loudspeaker with UV-resistant ABS housing, designed for indoor and outdoor speech and music sound reinforcement.

2-way system with 5.25" woofer and 1" tweeter for excellent speech intelligibility and balanced sound.

Three 100V power tapings (15/30/60W) plus 8-ohm operation.

Aluminium front grille with outdoor polyester powder coating.

V2A stainless steel mounting bracket for secure, flexible aiming.

Connection via rear screw terminal, protected by a cover plate with 2x PG11 cable glands.

Steel safety cable included in delivery.

IP66 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	60/30/15 (8)
Low impedance matching (Ohm):	167/333/667
Dimensions (mm):	180x180x194
Weight (kg):	2,70
Colour:	RAL 9005
Frequency response IEC268-5 (-10dB) (Hz):	100-24.000
Frequency range (Hz):	70-25.000
SPL IEC268-5, 1W/1m (dB):	89,9
Sensitivity EN54-24, 1W/4m (dB):	76,4
Dispersion angle -6 dB, 500 Hz:	360° h/v
Dispersion angle -6 dB, 1 kHz:	140°/154° h/v
Dispersion angle -6 dB, 2 kHz:	87° h/v
Dispersion angle -6 dB, 4 kHz:	103°/94° h/v