

Tender Specification

WA-S 06-165/T-EN54

Wall-mount loudspeaker, 6W, 100V, certified acc. to EN 54-24

Ultra-flat wall-mount loudspeaker for confined spaces and unobtrusive installations.

6W wide-range loudspeaker with 165mm chassis.

Impact-resistant, UV-resistant ABS housing in RAL 9016.

Magnetically attached grille for an unobtrusive, maintenance-friendly look.

Connection via WAGO terminal.

Flexible mounting: horizontal on the wall, horizontal between two walls and the ceiling, or vertical in a corner.

IP21 protection class.

RoHS compliant.

Technical Data:

Rated power/rated noise power 100 V (W):	6/3/1,5
Low impedance matching (Ohm):	1667/3333/6667
Dimensions (mm):	252x182x70
Weight (kg):	1,15
Colour:	RAL 9016
Frequency response IEC268-5 (-10dB) (Hz):	210-21.800
Frequency range (Hz):	184-23.300
SPL IEC268-5, 1W/1m (dB):	92,7
Sensitivity EN54-24, 1W/4m (dB):	79,0
Dispersion angle -6 dB, 500 Hz:	180° h/v
Dispersion angle -6 dB, 1 kHz:	160° h/v
Dispersion angle -6 dB, 2 kHz:	125° h/v
Dispersion angle -6 dB, 4 kHz:	89° h/v