



Tender specification

DA-P 10-260/T-EN54

Soundprojector, ABS-housing, 10 watts, 100 Volt, certified EN 54-24,

BS 5839 compliant

10W bi-directional soundprojector with two 130mm fullrange speaker, impact-resistant ABS-housing, ceramic block and thermal fuse in the provided junction box, PG7 cable gland, waterproofed speaker.

IP56 classification.

Mounting by the attached aluminium mounting bracket.

RoHS compliant

Technical Specifications:

Rated voice/noise power 100 V (Watt):	10/5/2,5
Low ohm connection (Ohm):	-
Dimensions (mm):	202 x 163 x 170
Weight (kg):	1,82
Colour:	RAL 9016
Frequency range (Hz):	100 - 20.000
Frequency response IEC268-5 (-10dB) (Hz):	90 - 25.000
SPL IEC268-5, 1 W/1 m (dB):	90,7
SPL IEC268-5, 1 W/4 m (dB):	78,7
SPL IEC268-5, Pmax./4 m (dB):	88,7
Sensitivity EN54-24, 1 W/4 m (dB):	85,6
Dispersion angle-6 dB, 500 Hz:	h / v 2x130° / 2x130°
Dispersion angle-6 dB, 1 kHz:	h / v 2x170° / 2x170°
Dispersion angle-6 dB, 2 kHz:	h / v 2x160° / 2x160°
Dispersion angle-6 dB, 4 kHz:	h / v 2x65° / 2x65°