



Tender specification

DA-P 20-130/T-EN54

**Sound projector, 20 W, 100 V, certified according EN 54-24,
compliant BS 5839**

Soundprojector, impregnated 130 mm full-range speaker, 100 V, equipped with ceramic block and thermal fuse, high-impact ABS-housing, IP54 protection standard.

Installation via an aluminium mounting-bracket.

Provided with an app. 1 m, five-pin cable. Not included in the delivery:

Cable gland for the signal cable from the amplifier.

RoHS-compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	20/10/5/2,5
Low ohm connection (Ohm):	-
Dimensions (mm):	∅ 145x222mm
Weight (kg):	1,44
Colour:	white
Frequency range (Hz):	150 - 20.000
Frequency response IEC268-5 (-10dB) (Hz):	120 – 21.000
SPL IEC268-5, 1 W/1 m (dB):	99,5
SPL IEC268-5, 1 W/4 m (dB):	87,5
SPL IEC268-5, Pmax./4 m (dB):	100,5
Sensitivity EN54-24, 1 W/4 m (dB):	75,0
Dispersion angle -6 dB, 500 Hz:	360°
Dispersion angle -6 dB, 1 kHz:	230°
Dispersion angle -6 dB, 2 kHz:	110°
Dispersion angle -6 dB, 4 kHz:	58°