



Tender specification

DA 10-130/T-EN54

**Aluminum sound projector, 10 Watt, 100 Volt, certified according to EN 54-24,
BS 5839 compliant**

10W unilaterally radiating sound projector with a 130mm full range speaker, aluminum housing, built-in ceramic black and thermal fuse, waterproofed chassis.

Can be painted in any other RAL color.

IP66 certified.

Mounting by screws to the vandal-proof foot of the speaker.

RoHS compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	10/6/3/1,5
Low ohm connection (Ohm):	-
Dimensions (mm):	∅ 166x197x108
Weight (kg):	1,9
Colour:	RAL 9010
Frequency range (Hz):	200 - 22.200
Frequency response (Hz):	150 - 23.500
SPL IEC268-5, 1 W/1 m (dB):	101,0
SPL IEC268-5, 1 W/4 m (dB):	89,0
SPL IEC268-5, Pmax./4 m (dB):	99,0
Sensitivity EN54-24, 1 W/4 m (dB):	78,9
Dispersion angle-6 dB, 500 Hz:	360°
Dispersion angle-6 dB, 1 kHz:	360°
Dispersion angle-6 dB, 2 kHz:	133°
Dispersion angle-6 dB, 4 kHz:	52°