



Tender specification

DL-BR 15-130/T plus-EN54

2-Way bassreflex ceiling speaker, 15 W, 100 V, certified according EN 54-24

Ceiling speaker, 100 V, waterproofed; UV-resistant high-impact PA-765 plastic housing, equipped with thermal fuse.

2-way-technology.

Mounting by 3 part screw system integrated in the speaker housing.

Installation via 4-pin screw terminal.

Equipped with a firedome for a higher passive security.

RoHS-compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	15 / 7,5 / 3,75 / 1,9
Low ohm connection (Ohm):	8
Dimensions (mm):	Ø 213 x 115
Weight (kg):	1,73
Colour:	RAL 9016
Frequency range (Hz):	100 - 22.800
Frequency response IEC268-5 (-10dB) (Hz):	87 - 23.600
SPL IEC268-5, 1 W/1 m (dB):	92,9
SPL IEC268-5, 1 W/4 m (dB):	80,9
SPL IEC268-5, Pmax./4 m (dB):	92,9
Sensitivity EN54-24, 1 W/4 m (dB):	74,2
Dispersion angle-6 dB, 500 Hz:	180°
Dispersion angle-6 dB, 1 kHz:	180°
Dispersion angle-6 dB, 2 kHz:	145°
Dispersion angle-6 dB, 4 kHz:	95°