



# Tender specification

**DL 06-130/T-EN54**

**Ceiling speaker, 6 W, 100 V, certified according EN 54-24,  
compliant BS 5839**

Metal ceiling speaker; 100 V, waterproofed 130 mm full range speaker, equipped with ceramic block and thermal fuse.

Metal-housing.

The wires are additional secured through a wire protection.

Mounting by 3 spring clamps with cropped leg spring, increased clamp force and shortened tension distance.

With firedome for a higher passive security.

RoHS-compliant.

## Technical Specifications:

Rated voice/noise power 100 V (Watt):	6/3/1,5
Low ohm connection (Ohm):	-
Dimensions (mm):	Ø 180x106
Weight (kg):	1,17
Colour:	RAL 9010
Frequency range (Hz):	350 - 13.800
Frequency response IEC268-5 (-10dB) (Hz):	84 - 16.300
SPL IEC268-5, 1 W/1 m (dB):	98,4
SPL IEC268-5, 1 W/4 m (dB):	86,4
SPL IEC268-5, Pmax./4 m (dB):	94,1
Sensitivity EN54-24, 1 W/4 m (dB):	80,0
Ceiling cut out (mm):	167
Dispersion angle-6 dB, 500 Hz:	180°
Dispersion angle-6 dB, 1 kHz:	180°
Dispersion angle-6 dB, 2 kHz:	120°
Dispersion angle-6 dB, 4 kHz:	65°