



Tender specification

MS 15-100/T black-EN54

Monitor speaker, 15 watt, 100 volt, certified according to EN 54-24

Monitor speaker with 2-way speaker system and thermal fuse.

Housing made of high-density ABS plastic, weather resistant.

Protected by protection class IP 33C against the risks of environmental influences.

The speaker is mounted by swivel bracket.

The connection is done by a stable 6-pin screw terminal with touch protection.

RoHS compliant.

Technical Specifications:

Rated voice/noise power 100 V (Watt):	15/7,5/3,75/1,8
Low ohm connection (Ohm):	8
Dimensions (mm):	∅ 210x130x120
Weight (kg):	1,75
Colour:	black
Frequency range (Hz):	105 - 23.500
Frequency response IEC268-5 (-10dB) (Hz):	82 - 23.500
SPL IEC268-5, 1 W/1 m (dB):	89,1
SPL IEC268-5, 1 W/4 m (dB):	77,1
SPL IEC268-5, Pmax./4 m (dB):	88,8
Sensitivity EN54-24, 1 W/4 m (dB):	70,5
Dispersion angle-6 dB, 500 Hz:	h=360° v=360°
Dispersion angle-6 dB, 1 kHz:	h=186° v=186°
Dispersion angle-6 dB, 2 kHz:	h=132° v=115°
Dispersion angle-6 dB, 4 kHz:	h=147° v=197°