

MS 30-130/T white-EN54

- Distinctive design
- Excellent sound
- IP 65

EN54

CE
13

EN 54-24:2008
Ref. Nr.: 011-13
ID-Code: SAA-LS11
1438-CPR-0998

ic audio GmbH, Boehringerstraße 14a,
68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

The compact monitor speaker impresses with its sophisticated design and its powerful sound. Perfectly suitable for installations where high sound quality is needed.

The 30W powered speaker is equipped with a high-quality 2-way system and a 100V transformer with 3 power adjustments. Low-impedance operation with 8 ohms is possible. The impact-resistant, UV-resistant ABS plastic housing in RAL 9016 assures enduring stability. For additional reliability, a wetness impregnation of the speaker is provided.

The speaker is also secured with protection class IP 65 against the risks of environmental influences. A comfortable connection of the speaker is made possible by a stable screw terminal with contact protection. Quick and easy mounting with wall mounting bracket.

Product	MS 30-130/T white-EN54
Article No	20122645

Acoustics

Power	30/15/7,5/3,75 (8ohm) W
Impedance (100V)	333/667/1333/2667 ohm
Speaker ø	130 mm
Frequency Range	60 - 24.000 Hz
Frequency Response	50 - 25.000 Hz
SPL 1W/1m, peak	87,4 dB
SPL 1W/4m, peak	75,4 dB
SPL Pmax/4m, peak	90,1 dB
SPL IEC268-5, 1W/1m	82,4 dB
SPL IEC268-5, Pmax/1m	97,2 dB
Sensitivity EN54-24, 1W/1m	82,4 dB
Sensitivity EN54-24, 1W/4m	70,4 dB
Dispersion -6dB, 500Hz	360 ° h/v
Dispersion -6dB, 1KHz	200°/160° h/v
Dispersion -6dB, 2KHz	130°/100° h/v
Dispersion -6dB, 4KHz	120°/40° h/v

Connections and Housing

Connector	6-pin screw terminal
Terminal Diameter	2,5 mm
Maximum Cable Passage	4,9 mm²
Max. cable cross section loop	2x1,2mm²
Temperature Range	-25 / +80 °C
Type A/B	B
Dimensions	262x160x153 mm
Weight (net)	2,80 kg
Housing	ABS
Colour	RAL 9016
Mounting	Swivel bracket
IP Rating	IP65


Certification

Ref. Nr.	011-13
ID-Code	SAA-LS11
Certificate Number	1438-CPR-0998

Product Attributes




Technical Drawing




Frequency Response Diagram

Sensitivity




SPL Max




Isobar

Horizontal




Vertical




Polar Diagram


Polar Diagram 500Hz




Polar Diagram 4000Hz




Polar Diagram 1000Hz



Polar Diagram 8000Hz



Polar Diagram 2000Hz



ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.

Article No: 20122645
Packing Unit: 8