


DL-FF 06-165/T-EN54

- quick mounting
- built-in dome for concrete ceilings
- ballproof



EN 54-24:2008

Ref. Nr.: 014-14

ID-Code: SAA-LS14

1438-CPR-0384

ic audio GmbH, Boehringerstraße 14a,
D-68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

The 6W powered speaker is equipped with a 165mm full-range loudspeaker chassis and a 100V transformer with 3 power adjustments. The powder-coated metal version with a perforated grid cover in RAL 9010 guarantees lasting stability. For additional reliability, a 2-pin ceramic block, and a thermal fuse is provided and the speaker chassis is impregnated against wetness.

The speaker is also secured with protection class IP 21C against the security risks of environmental influences. Quick and easy mounting with spring clamps and short tension distance. The connecting cables can be supplied by rubber grommets in the fire dome.

This speaker is suitable for installation in concrete ceilings. Special paint of the speaker in 4-digit RAL- or NCS-colour is available at extra cost.

The speaker is also compliant with the British Standard BS 5839, Part 8.

Product	DL-FF 06-165/T-EN54
Artikel Nr.	20142814

Acoustics

Power	6/3/1,5 W
Impedance (100V)	1667/3333/6667 ohm
Speaker ø	165 mm
Frequency Range	125 - 23.500 Hz
Frequency Response	100 - 23.500 Hz
SPL 1W/1m, peak	104,5 dB
SPL 1W/4m, peak	92,5 dB
SPL Pmax/4m, peak	100,2 dB
SPL IEC268-5, 1W/1m	92,0 dB
SPL IEC268-5, Pmax/1m	99,8 dB
Sensitivity EN54-24, 1W/1m	92,0 dB
Sensitivity EN54-24, 1W/4m	80,0 dB
Dispersion -6dB, 500Hz	h/v 180°
Dispersion -6dB, 1KHz	h/v 180°
Dispersion -6dB, 2KHz	h/v 97,5°
Dispersion -6dB, 4KHz	h/v 44°

Connections and Housing

Connector	2-pin ceramic block
Terminal Diameter	3,2 mm
Maximum Cable Passage	8 mm ²
Temperature Range	-10 / +55 C°
Type A/B	A
Dimensions	230x98,5 mm
Ceiling Cut-out	201 mm
Weight (net)	1,65kg
Housing	metal
Colour	RAL 9010
Mounting	Quick fit mounting
IP Rating	IP21

Certification

Ref. Nr.	014-14
ID-Code	SAA-LS14
Certificate Number	1438-CPR-0384


Product Attributes



Technical Drawing



DL-FF 06-165/T-EN54




all dimensions are in mm

Technical Drawing




DL-FF 06-165/T-EN54




all dimensions are in mm

Frequency Response Diagram


Sensitivity



SPL Max




Isobar




Polar Diagram


Polar Diagram 500Hz




Polar Diagram 4000Hz




Polar Diagram 1000Hz



Polar Diagram 8000Hz



Polar Diagram 2000Hz



ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.



Artikel Nr. : 20142814
Packing Unit: 8

