



WA 06-165/T-EN54W

- Softline-design
- shock-resistant housing
- WAGO 221 connector



EN 54-24:2008
Ref. Nr.: 007-18
ID-Code: SAA-LS07
1438-CPR-0231

ic audio GmbH, Boehringerstraße 14a,
68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

The 6W powered speaker is equipped with a 165mm full-range loudspeaker chassis and a 100V transformer with 3 power adjustments. The high-density, shock-resistant MDF wood housing in RAL 9010 provides a low resonance sound. A sturdy front grille made of steel guarantees enduring stability. For additional reliability, the speaker chassis is impregnated against wetness. Fast and easy installation by WAGO 221 connector.

The speaker is also secured with the high protection class IP 54 against the security risks of environmental influences.

The reliable spring clamp on the rear plate ensures quick mounting on walls.

Product	WA 06-165/T-EN54W
Artikel Nr.	20102197-W

Acoustics

Power	6/3/1,5 W
Impedance (100V)	1667/3333/6667 ohm
Speaker ø	165 mm
Frequency Range	197 - 21.900 Hz
Frequency Response	175 - 23.500 Hz
SPL 1W/1m, peak	100,6 dB
SPL 1W/4m, peak	88,6 dB
SPL Pmax/4m, peak	96,3 dB
SPL IEC268-5, Pmax/1m	100,8 dB
Sensitivity EN54-24, 1W/4m	79,5 dB
Dispersion -6dB, 500Hz	h=180° v=180°
Dispersion -6dB, 1KHz	h=83° v=74°
Dispersion -6dB, 2KHz	h=100° v=115°
Dispersion -6dB, 4KHz	h=55° v=53°

Connections and Housing

Connector	WAGO 221 connector
Terminal Diameter	2,3 mm
Maximum Cable Passage	4 mm ²
Max. cable cross section loop	4 mm ²
Temperature Range	-20 / +80 °C
Dimensions	254x195x81 mm
Weight (net)	1,73 kg
Housing	MDF
Colour	RAL 9010
Mounting	spring clamp
IP Rating	IP54

Certification

Ref. Nr.	007-18
ID-Code	SAA-LS07
Certificate Number	1438-CPR-0231


Product Attributes



Technical Drawing




WA 06-165/T-EN54W




all dimensions are in mm

Frequency Response Diagram

Sensitivity




SPL Max




Isobar

Horizontal




Vertical




Polar Diagram


Polar Diagram 500Hz




Polar Diagram 4000Hz




Polar Diagram 1000Hz



Polar Diagram 8000Hz



Polar Diagram 2000Hz



ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.



Artikel Nr. : 20102197-W
Packing Unit: 8

