



DL-SE 06-100/T-EN54

- splash-proof
- frameless design
- WAGO connector 221

EN54

CE
25

EN 54-24:2008
Ref. Nr.: 006-27
ID-Code: SAA-LS27
1438-CPR-0642

ic audio GmbH, Boehringerstraße 14a,
68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

The DL-SE 06-100/T-EN54 is a splash-proof version of the SE-Series which is perfect for installation in bathrooms, pool areas, e.g. The 6W powered speaker is equipped with a 100mm full-range loudspeaker and a 100V transformer with 3 power adjustments. The powder-coated metal in RAL 9016 guarantees long-term stability.

The speaker is secured with protection class IP 54 against the risks of environmental influences. For additional reliability, the speaker is impregnated against wetness. Fast and easy installation by WAGO 221 connector and strong spring clamps with protective caps for vibration damping. The connecting cables can be supplied through rubber grommets in the fire dome.

Special paint of the speaker in 4-digit RAL- or NCS- colour is available at extra cost. The ABS fire dome is included in the delivery.

This speaker is suitable for a ceiling strength of about 1-45 mm. Our specification is primarily related to solid ceilings, for ceilings with soft materials higher ceiling thicknesses could be necessary. In addition, stronger cables and other fittings may also result in changes in the appropriate setup. Regarding the variety of materials and manufacturers, we recommend building a sample of the speaker to match the requirements accurately.

Product	DL-SE 06-100/T-EN54
Article No	20206395

Acoustics

Power	6/3/1,5 W
Impedance (100V)	1667/3333/6667 ohm
Speaker ø	100 mm
Frequency Range	230 - 12.000 Hz
Frequency Response	220 - 14.000 Hz
SPL 1W/1m, peak	95 dB
SPL 1W/4m, peak	83 dB
SPL Pmax/4m, peak	90 dB
SPL IEC268-5, 1W/1m	91 dB
SPL IEC268-5, Pmax/1m	96,0 dB
Sensitivity EN54-24, 1W/1m	88,1 dB
Sensitivity EN54-24, 1W/4m	68,5 dB
Dispersion -6dB, 500Hz	180° h/v
Dispersion -6dB, 1KHz	180° h/v
Dispersion -6dB, 2KHz	180° h/v
Dispersion -6dB, 4KHz	81° h/v

Connections and Housing

Connector	WAGO 221 connector
Terminal Diameter	2,3 mm
Maximum Cable Passage	4 mm²
Max. cable cross section loop	4 mm²
Temperature Range	-10 / +55 C°
Type A/B	A
Dimensions	140x94 mm
Ceiling Cut-out	129 mm
Weight (net)	0,68 kg
Housing	metal
Colour	RAL 9016
Mounting	spring clamp
IP Rating	IP54

Certification

Ref. Nr.	006-27
ID-Code	SAA-LS27
Certificate Number	1438-CPR-0642


Product Attributes



Technical Drawing

ic audio


DL-SE 06-100/T-EN54




all dimensions are in mm

Frequency Response Diagram


Sensitivity



SPL Max




Isobar



Level
[dB]
0
-1,25
-2,5
-3,75
-5
-6,25
-7,5
-8,75
-10
31,5 Hz
63 Hz
125 Hz
250 Hz
500 Hz
1 kHz
2 kHz
4 kHz
8 kHz
16 kHz
-90
-60
-30
0 (Front)
30
60
90

Polar Diagram


Polar Diagram 500Hz




Polar Diagram 4000Hz




Polar Diagram 1000Hz



Polar Diagram 8000Hz



Polar Diagram 2000Hz



ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.

Article No: 20206395
Packing Unit: 12