

DL-E 06-130/T-EN54-C

- high sound pressure level
- low mounting depth
- antistatic plastic contact protection



EN 54-24:2008

Ref. Nr.: 012-13

ID-Code: SAA-LS12

1438-CPR-0347

ic audio GmbH, Boehringerstraße 14a,
68307 Mannheim, Germany

CE-Symbol gemäß Richtlinie 93/68EWG

The 6W powered speaker is equipped with a 130mm full-range loudspeaker, a 100V transformer with 3 power adjustments and a DC blocking capacitor (1µF, 250V). The powder-coated metal version in RAL 9016 guarantees lasting stability. Thanks to an innovative airflow system, the DL-E provides sound characteristics which are attributed to a conventional bass speaker. An extremely flat construction method allows a low mounting depth of only 70mm, with less than 1 kg product weight. For additional reliability, the speaker is impregnated against wetness.

The speaker is also secured with protection class IP 21C against the security risks of environmental influences. Quick and easy mounting with spring clamps and short tension distance. Perfectly suitable for installations where the installation depth is very limited.

Special paint of the speaker in 4-digit RAL- or NCS-colour is available at extra cost.

The innovative PET-plastic contact protection is included in the delivery and protected by a European patent (publication no. **2768238**).

This speaker is suitable for a ceiling strength of about 3-45 mm. Our specification is primarily related to solid ceilings, for ceilings with soft materials higher ceiling thicknesses could be necessary. In addition, stronger cables and other fittings may also result in changes in the appropriate setup. With regard to the variety of materials and manufacturers, we recommend building a sample of the speaker to match the requirements accurately.

Product	DL-E 06-130/T-EN54-C
Artikel Nr.	20183524-C

Acoustics

Power	6/3/1,5 W
Impedance (100V)	1667/3333/6667 ohm
Speaker ø	130 mm
Frequency Range	104 - 17.200 Hz
Frequency Response	57 - 24.000 Hz
SPL 1W/1m, peak	98,3 dB
SPL 1W/4m, peak	86,3 dB
SPL Pmax/4m, peak	94 dB
SPL IEC268-5, 1W/1m	87,0 dB (plastic) 86,0 dB (metal)
SPL IEC268-5, Pmax/1m	94,8 dB
Sensitivity EN54-24, 1W/1m	86,8 dB
Sensitivity EN54-24, 1W/4m	74,8 dB (plastic) 74,2 dB (metal)
Dispersion -6dB, 500Hz	180° plastic/metal
Dispersion -6dB, 1KHz	180° plastic/metal
Dispersion -6dB, 2KHz	140° plastic/metal
Dispersion -6dB, 4KHz	85°/84° plastic/metal

Connections and Housing

Connector	4-pin screw terminal
Terminal Diameter	2,5 mm
Maximum Cable Passage	4,9 mm ²
Max. cable cross section loop	2x1,2 mm ²
Temperature Range	-10 / +55 C°
Type A/B	A
Dimensions	181x66 mm (plastic) 181x81 mm (metal)
Ceiling Cut-out	156 mm
Weight (net)	0,51 kg (plastic) 0,72 kg (metal)
Housing	metal
Colour	RAL 9016
Mounting	spring clamp
IP Rating	IP21

Certification

Ref. Nr.	012-13
ID-Code	SAA-LS12
Certificate Number	1438-CPR-0347



Product Attributes



Technical Drawing




DL-E 06-130/T-EN54-C




all dimensions are in mm

Frequency Response Diagram


Sensitivity



SPL Max




Isobar




Polar Diagram


Polar Diagram 500Hz




Polar Diagram 4000Hz




Polar Diagram 1000Hz



Polar Diagram 8000Hz



Polar Diagram 2000Hz



ic audio loudspeakers are tested and classified according to the IEC standard 60529 (degree of protection by enclosure) against the penetration of foreign objects and moisture. The classification is conforming to standards through characterization with a fixed code. This code consists of the letters IP (International Protection) followed by two digits. The first digit indicates the degree of protection against dust and the second digit the degree of protection against water. Please note that the testing of the products has been carried out in laboratory conditions which are not always 100% comparable with the conditions of different installation environments. This protection can be reduced due to normal wear and tear depending on the installation environment.

RoHS compliant (2011/65/EU)

The IP rating specified is based on ic audio test results, not on CNBOP-PIB test results. Certification only verifies the minimum requirements for EN54-24 compliance.



Artikel Nr. : 20183524-C
Packing Unit: 12

