DK-MH 30/T PLUS-EN54

2-way music-horn for Voice Alarm, 30W power, certified EN 54-24



Technical Data

Colour	RAL 7035
Dimensions	370x255x291 mm
Dispersion -6dB, 500Hz	190° (h) 205° (v)
Dispersion -6dB, 1KHz	70 °(h) 90° (v)
Dispersion -6dB, 2KHz	85° (h) 90° (v)
Dispersion -6dB, 4KHz	80° (h) 110° (v)
Frequency Range	237 - 21.100 Hz
Frequency Response	65 - 24.000 Hz
Power	30/15/7,5/3,75 W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06

DK-MH 30/T PLUS-EN54

4 260590 180094

Mounting Instruction

1. Mount the U-bracket on the ceiling with the appropriate screws for the surface.
2. If necessary, remove the speaker enclosure from the U-bracket.
3. Insert the loudspeaker cable through the cable entry of the previously removed rear wall of the housing.
4. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
5. Carefully reinsert the back panel into the housing.

Power Tappings

Black	Blue	Yellow	Green	Brown
COM	30	15	7,5	3,75

CE 11

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-13
ID-Code:SAA-LS03
1438-CPR-1177

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06