

DL-K16-130/T-EN54

Sphere speaker for Voice Alarm, power 16W, certified
EN 54-24



Technical Data

Colour	RAL 9010
Dimensions	185x157 mm
Dispersion -6dB, 500Hz	h/v 360°
Dispersion -6dB, 1KHz	h/v 196°
Dispersion -6dB, 2KHz	h/v 132°
Dispersion -6dB, 4KHz	h/v 171°
Sensitivity EN54-24, 1W/1m	85,0 dB
Sensitivity EN54-24, 1W/4m	73,0 dB
Frequency Range	130 - 13.300 Hz
Frequency Response	130 - 23.500 Hz
SPL IEC268-5, 1W/1m	85,0 dB
SPL EN54-24, Pmax/4m	86,5 dB
Power	16/8/4 W



DL-K16-130/T-EN54

Mounting Instruction

- 1. Hang the spherical loudspeaker on a hook on the ceiling by the pull release.
- 2. Connect the incoming line to the terminal in the canopy.
- 3. Push the canopy all the way up to the ceiling until the clamp is covered.

Power Tappings

Red	Blue	Yellow	White
COM	16	8	4

TO MAKE PEOPLE LISTEN



CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire
detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:005-13
ID-Code:SAA-LS05
1438-CPD-0325