DL-K16-130/T-EN54

Sphere speaker for Voice Alarm, power 16W, certified EN 54-24



Technical Data

Colour	RAL 9010
Dimensions	185x157 mm
Dispersion -6dB, 500Hz	h/v 360°
Dispersion -6dB, 1KHz	h/v 196°
Dispersion -6dB, 2KHz	h/v 132°
Dispersion -6dB, 4KHz	h/v 171°
Frequency Range	130 - 13.300 Hz
Frequency Response	130 - 23.500 Hz
Power	16/8/4 W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06

DL-K16-130/T-EN54

4 260590 180452

Mounting Instruction

1. Hang the spherical loudspeaker on a hook on the ceiling by the pull release.
2. Connect the incoming line to the terminal in the canopy.
3. Push the canopy all the way up to the ceiling until the clamp is covered.

Power Tappings

Red	Blue	Yellow	White
COM	16	8	4

CE 13

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:005-13
ID-Code:SAA-LS05
1438-CPD-0325

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06