



DA 10-130/T-EN54

Directional sound projector for Voice Alarm, 10W power, certified EN 54-24

Technical Data

Colour	RAL 9010
Dimensions	161x197x166 mm
Dispersion -6dB, 500Hz	360° v/h
Dispersion -6dB, 1KHz	230° v/h
Dispersion -6dB, 2KHz	120° v/h
Dispersion -6dB, 4KHz	50° v/h
Sensitivity EN54-24, 1W/1m	90,9 dB
Sensitivity EN54-24, 1W/4m	81,0 dB
Frequency Range	200 - 22.200 Hz
Frequency Response	150 - 23.500 Hz
SPL IEC268-5, 1W/1m	93,0 dB
SPL EN54-24, Pmax/4m	90,0 dB
Power	10/6/3/1,5 W



DA 10-130/T-EN54

Mounting Instruction

- 1. Prepare the mounting holes for the mounting base on the wall or ceiling.
- 2. Insert the loudspeaker cable through the cable entry of the mounting plate / rear wall of the housing.
- 3. Connect the loudspeaker cable to the terminals 100V and COM.
If necessary, select a different power tapping.
- 4. Mount the mounting base on the previously prepared fixing holes with screws suitable for the surface.

Power Tappings

Black	Brown	Red	White	Green
COM	10	6	3	1,5

TO MAKE PEOPLE LISTEN



CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire
detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-14
ID-Code:SAA-LS14
1438-CPR-1000