DA 10-130/T-EN54

Directional sound projector for Voice Alarm, 10W power, certified EN 54-24



Mechanical Data

Colour	RAL 9010
Dimensions	161x197x166 mm
Weight (net)	1,84 kg
Power	10/6/3/1,5 W
Connector	2-pin ceramic block
Terminal Diameter	3,2 mm
Maximum Cable Passage	8 mm^2
Mounting	screws

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08

DA 10-130/T-EN54

Mounting Instruction

1. Prepare the mounting holes for the mounting base on the wall or ceiling.
2. Insert the loudspeaker cable through the cable entry of the mounting plate / rear wall of the housing.
3. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
4. Mount the mounting base on the previously prepared fixing holes with screws suitable for the surface.

Power Tappings

Black	Brown	Red	White	Green
COM	10	6	3	1,5

CE
24

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-14
ID-Code:SAA-LS14
1438-CPR-1000

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08