# DA 10-260/T-EN54

Bi-directional sound projector for Voice Alarm, 10W power, certified EN 54-24



## Mechanical Data

| | |
|---|---|
| Colour | RAL 9010 |
| Dimensions | 199x171x161 mm |
| Weight (net) | 2,30 kg |
| Power | 10/6/3/1,5 W |
| Connector | 2-pin ceramic block |
| Terminal Diameter | 3,2 mm |
| Maximum Cable Passage | 8 $mm^2$ |
| Mounting | screws |

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08

# DA 10-260/T-EN54

4 260590 180025

## Mounting Instruction

1. Prepare the mounting holes for the mounting base on the wall or ceiling.
2. Insert the loudspeaker cable through the cable entry of the mounting plate / rear wall of the housing.
3. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
4. Mount the mounting base on the previously prepared fixing holes with screws suitable for the surface.

## Power Tappings

| Black | Brown | Red | White | Green |
|---|---|---|---|---|
| COM | 10 | 6 | 3 | 1,5 |

CE 24

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-14
ID-Code:SAA-LS14
1438-CPR-1000

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08