DL-A-AB 06-100/T-EN54

Surface-mounted ceiling speaker for Voice Alarm, A/B-cabling, 2x6 power, certified EN 54-24



Mechanical Data

Colour	RAL 9010
Dimensions	208x89 mm
Weight (net)	1,90 kg
Power	2x6/3/1,5 W
Connector	2-pin ceramic block
Mounting	Screws

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-27


DL-A-AB 06-100/T-EN54

4 260590 180407

Mounting Instruction

1. Fix the mounting plate on the wall or ceiling using screws suitable for the surface.
2. Push the loudspeaker cable through the cable entry of the mounting plate.
3. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
4. Place the baffle on the mounting plate and fasten it with the enclosed screws.

Please note: To avoid damage, we recommend loosening the cable lug with a flat-blade screwdriver when changing the cable to a different power tapping.



CE
16

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:004-15
ID-Code:SAA-LS04
1438-CPR-0448

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-27