WU-SW 06-165/T METAL-EN54

Baffle speaker for Voice Alarm, 6W power, certified EN 54-24



Technical Data

Colour	RAL 9005
Dimensions	300 x 200 x 76 mm
Dispersion -6dB, 500Hz	h=180° v=180°
Dispersion -6dB, 1KHz	h=180° v=180°
Dispersion -6dB, 2KHz	h=110° v=120°
Dispersion -6dB, 4KHz	h=60° v=60°
Frequency Range	272 - 23.700 Hz
Frequency Response	106 - 23.500 Hz
Power	6/3/1,5 W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07

WU-SW 06-165/T METAL-EN54

4 260590 180599

Mounting Instruction

1. Place the loudspeaker face down on the ceiling grid.
2. Connect the speaker cable to the 4 pin screw terminal.
3. Use a screwdriver to fix the connection of the cables to the screw terminal.
4. Place the enclosed cable housing on the screw terminal to ensure permanent protection.

CE
15

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:018-15
ID-Code:SAA-LS18
1438-CPR-0270

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07