DL-S 50-165/T PLUS-EN54

2-way ceiling speaker for Voice Alarm, 50W power, certified EN 54-24



Mechanical Data

Colour	RAL 9016
Dimensions	264 x 239 mm
Ceiling Cut-out	238 mm
Weight (net)	3,73 kg
Power	50/25/12,5/6,25/ (8) W
Connector	4-pin screw terminal
Terminal Diameter	2,5 mm
Maximum Cable Passage	4,9 mm²
Mounting	Screw system

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08

DL-S 50-165/T PLUS-EN54

4 260590 183798

Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Connect the connection cable with the Phoenix terminal and plug it into the pin header of the speaker.
3. Attach the strain relief to the connection cable.
4. Mount the loudspeaker flush in the ceiling cut-out and tighten the four mounting screws behind the magnetic grille.
5. For power adjustments, remove the grille, set the desired power on the rotary switch and place the magnetic grille back on the front of the speaker.

CE
19

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:009-19
ID-Code:SAA-LS09
1438-CPR-0431

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08