DL-BR-SUB120/T-EN54

Ceiling subwoofer for Voice Alarm, 120W power, compliant EN 54-24



Technical Data

Colour	RAL 9016
Dimensions	320 x 255 mm
Ceiling Cut-out	302 mm
Frequency Range	32-280 Hz (-10 dB)
Frequency Response	50-200 Hz (+-3dB)
Power	120/60/30/15/ (4) W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07

DL-BR-SUB120/T-EN54

4 260590 183811

Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Open the metal cover on the back.
3. Guide the connection cable through the rubber grommet of the metal cover.
4. Connect the connection cables to the screw terminal. Screw the wiring to the terminal with a screwdriver.
5. Plug the terminal into the pin strip on the back of the speaker. Screw the metal cover back on.
6. Remove the grille with the enclosed mounting hook.
7. Insert the speaker into the ceiling until the speaker ring on the front touches the ceiling. Use the installation screws on the side of the speaker to fix it in the ceiling.
8. Replace the speaker grille.

CE

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:020-19
ID-Code:SAA-LS20

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07