Operation, Installation and Maintenance Manual

DL-FF 06-130/T MED

Ceiling speaker for marine application, 6W power, certified MED/1.44b



Mechanical Data

Colour	RAL 9010
Dimensions	178x81 mm
Ceiling Cut-out	145 mm
Weight (net)	1,20 kg
Power	6/3/1,5 W
Connector	cable
Mounting	screw system

Environmental Category: Category A (IEC 60945 - Protected Equipment)

0098/2026

(EU) 2026/1434, item No. MED/1.44b. SOLAS 1974 as amended, Regulation II-2/12,21,22, III/4, 6 & X/3, LSA Code VII, HSC Code 4,8, IMO MSC.1/Circ. 808, 1369/Add.1
suitable for:

- Cargo ships
- Passenger ships without SRtP
- Passenger ships with SRtP

Compass Safe Distance: 1.25 m (standard compass), 0.85 m (steering and emergency compass) to prevent magnetic interference with navigational instruments

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26

DL-FF 06-130/T MED

Mounting Instruction

1. Route the cable through the cable entry.
2. Secure the fire dome to the ceiling using screws or nails.
3. Connect the cable to the terminal.
4. Insert the grille into the central threaded hole of the housing and turn it clockwise.

An integrated thermal fuse automatically disconnects the loudspeaker driver in the event of excessive heat (e.g. due to fire or driver failure), preventing a short circuit across the 100V line. Do not bypass or remove the thermal fuse under any circumstances. Verify the integrity of the connection cable during periodic maintenance.

CE
26

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)

ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

MED certification
Notified
Body No.: 0098
Certificate No.:
MEDB0000AMS

TO MAKE PEOPLE LISTEN

Document No.: 260922 Manual_ DL-FF 06-130/T MED

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26