DK10/T-EN54-PG

Horn speaker for Voice Alarm, 10W power, certified EN 54-24



Technical Data

Colour	RAL 7035
Dimensions	142x256 mm
Dispersion -6dB, 500Hz	h/v 360°
Dispersion -6dB, 1KHz	h/v 360°
Dispersion -6dB, 2KHz	h/v 105°
Dispersion -6dB, 4KHz	h/v 50°
Frequency Range	569 - 7.000 Hz
Frequency Response	370 - 13.600 Hz
Power	10/5/2,5/1,25 (20) W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08

DK10/T-EN54-PG

4 260590 184832

Mounting Instruction

1. Mount the U-bracket on the ceiling with the appropriate screws for the surface.
2. If necessary, remove the speaker enclosure from the U-bracket.
3. Insert the loudspeaker cable through the cable entry of the previously removed rear wall of the housing.
4. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
5. Carefully reinsert the back panel into the housing.

EQ Settings

EQ Setting Frequency [Hz]	Relative level to 1000 Hz [dB]	EQ Setting Frequency [Hz]	Relative level to 1000 Hz [dB]	EQ Setting Frequency [Hz]	Relative level to 1000 Hz [dB]	EQ Setting Frequency [Hz]	Relative level to 1000 Hz [dB]
20	0	80	0	315	+4	1250	0
25	0	100	-12	400	+8	1600	0
31,5	0	125	-12	500	+8	2000	0
40	0	160	-12	630	+6	2500	0
50	0	200	-8	800	+8	3150	+4
63	0	250	-1	1000	0	4000	+8
80	0	315	+4	1250	0	5000	+12
100	-12	400	+8	1600	0	6300	+12

TO MAKE PEOPLE LISTEN

CE
20

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-13
ID-Code:SAA-LS03
1438-CPR-1177

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08