

DA-D 20-130/T-EN54

Sound projector for Voice Alarm, 20W power, certified

EN 54-24



Technical Data

Colour	RAL 9016
Dimensions	169x 283,5mm
Dispersion -6dB, 500Hz	h/v 360°
Dispersion -6dB, 1KHz	h/v 155° / 220°
Dispersion -6dB, 2KHz	h/v 95° / 85°
Dispersion -6dB, 4KHz	h/v 80° / 85°
Sensitivity EN54-24, 1W/4m	76,4 dB
Frequency Range	142 - 14.300 Hz
Frequency Response	112 - 15.800 Hz
SPL IEC268-5, 1W/1m	92,0 dB
SPL EN54-24, Pmax/4m	88,0 dB
Power	20/10/5 W



DA-D 20-130/T-EN54

Mounting Instruction

1. Remove the rear cover.
2. Guide the speaker cable through the cable gland.
3. Connect the speaker cable to the ceramic clamp.
4. Replace the cover on the back of the speaker.
5. Attach the bracket to the wall. Fix the bracket with screws.

Power Tappings

Black	Brown	Red	Yellow
COM	20	10	5



CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire
detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
D-68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:021-32
ID-Code:SAA-LS32
1438-CPR-0758