PRO 250-300/T PLUS BLACK-EN54

2-way coaxial horn speaker for Voice Alarm, 250W power, certified EN 54-24



Mechanical Data

Colour	RAL 9005
Dimensions	390x425x418 mm
Weight (net)	20,85 kg
Power	250/125/63W (8ohm)
Connector	4-pin screw terminal
Terminal Diameter	2,5 mm
Maximum Cable Passage	4,9 mm²
Mounting	Mounting bracket

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26

PRO 250-300/T PLUS BLACK-EN54

4 260590 185099

Mounting Instruction

1. Mount the inclination-adjustable stainless steel bracket on the ceiling. See the drawing below to set the right angle.
2. Attach the speaker with the screws to the stainless steel bracket.
3. Remove the rear cover of the loudspeaker.
4. Guide the loudspeaker cable through the cable gland.
5. Connect the loudspeaker cable to the rear terminal.
   Make power adjustments at the rear of the speaker as needed.
6. Replace the rear cover.

CE
22

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:022-04
ID-Code:SAA-LS28
1438-CPR-0814

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26

PRO 150-200/T EN54





