DL-SE 06-66/T-EN54

Ceiling speaker for Voice Alarm, 6W power, certified EN 54-24



Technical Data

Colour	RAL 9016
Dimensions	105x83 mm
Ceiling Cut-out	90 mm
Dispersion -6dB, 500Hz	180° h/v
Dispersion -6dB, 1KHz	180° h/v
Dispersion -6dB, 2KHz	180° h/v
Dispersion -6dB, 4KHz	127° h/v
Frequency Range	250 - 16.000 Hz
Frequency Response	220 - 17.000 Hz
Power	6/3/1,5 W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07

DL-SE 06-66/T-EN54

4 260590 185952

Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Loosen the screw on the back of the speaker and remove the rear housing.
3. Guide the speaker cable through the rubber grommets.
4. Connect the speaker cables to the WAGO terminal.
5. Carefully close the connector housing again and secure it with the screw.
6. Tension the springs upwards and insert the loudspeaker with the springs first into the ceiling cut-out.
7. Carefully relieve the tension on the springs until the speaker is centred in the ceiling cut-out.

CE
24

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:052-26
ID-Code:SAA-LS62
1438-CPR-1262

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-07