DL-S15-100/T PLUS WHITE-EN54

2-way ceiling speaker for Voice Alarm, 15W power, certified EN 54-24



Mechanical Data

Colour	RAL 9016
Dimensions	242x108 mm
Ceiling Cut-out	210 mm
Weight (net)	1,87 kg
Power	15/7.5/3.75 (8) W
Connector	6-pin screw terminal
Mounting	screw system

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08

DL-S15-100/T PLUS WHITE-EN54

4 260590 186096

Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Remove the speaker grille, which is fixed by magnetic fastening.
3. Guide the connection cable through the cable passage with the rubber grommet.
4. Connect the speaker cable to the screw terminal at the front of the speaker. If necessary, use the rotary switch to select a different power adjustment.
5. Plug the terminal into the pin strip on the front of the speaker.
6. Attach a safety cable to the eyelet on the side of the speaker (not supplied).
7. Insert the speaker into the ceiling until the speaker ring on the front touches the ceiling.
8. Use the three installation screws on the side of the speaker to fix it in the ceiling.
9. Reattach the speaker grille.

CE
25

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:024-15
ID-Code:SAA-LS15
1438-CPR-1089

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-08