DL-D 30-130 WHITE DANTE

2-way active ceiling speaker with Dante® interface, 30W power



Technical Data

Colour	RAL 9016
Dimensions	322x128 mm
Dispersion -6dB, 500Hz	180° h/v
Dispersion -6dB, 1KHz	180° h/v
Dispersion -6dB, 2KHz	90°/96° h/v
Dispersion -6dB, 4KHz	27°/57° h/v
Frequency Range	72 - 21.500 Hz
Frequency Response	63 - 25.000 Hz
Power	30W

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06

DL-D 30-130 WHITE DANTE

4 260590 186294

Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Connect the connection cable to the desired port.
3. Remove the speaker grille, which is held in place by magnetic fasteners.
4. Insert the speaker into the ceiling until the speaker ring on the front touches the ceiling.
5. Use the three installation screws on the side of the speaker to fix it in the ceiling.
6. Reattach the speaker grille.

For software configuration details and further information go to audinate.com

CE
25

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)

ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-06