PRO 60-130/T PLUS WHITE-EN54

2-way coaxial speaker for Voice Alarm, 60W power, certified EN 54-24



Mechanical Data

Colour	RAL 9016
Dimensions	180x180x194 mm
Weight (net)	2,70 kg
Power	60/30/15 W (8ohm)
Connector	4-pin screw terminal
Terminal Diameter	2,5 mm
Maximum Cable Passage	4,9 mm
Mounting	Mounting bracket

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-31

PRO 60-130/T PLUS WHITE-EN54

4 260590 186539

Mounting Instruction

1. Mount the inclination-adjustable stainless steel bracket on the ceiling.
2. Attach the speaker with the screws to the stainless steel bracket.
3. Remove the rear cover of the loudspeaker.
4. Guide the loudspeaker cable through the cable gland.
5. Connect the loudspeaker cable to the rear terminal.
   Make power adjustments at the rear of the speaker as needed.
6. Replace the rear cover.

CE

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
:
:

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-31