# DL-SE 06-165/T-EN54 SAFE STR

Ceiling speaker for voice alarm, 6W power, EN 54-24 certified



## Mechanical Data

| | |
|---|---|
| Colour | RAL 9016 |
| Dimensions | 220x104 mm |
| Ceiling Cut-out | 188 mm |
| Weight (net) | 1,18 kg |
| Power | 6/3/1,5 W |
| Connector | 4-pin ceramic block |
| Maximum Cable Passage | 8 mm² |
| Mounting | spring clamp |

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-11-19

# DL-SE 06-165/T-EN54 SAFE STR

4 260590 186140

## Mounting Instruction

1. Create the necessary ceiling cut-out and check the installation depth.
2. Loosen the screws of the terminal cover, slide it to the right and remove the cover.
3. Guide the speaker cable through the cable gland of the terminal cover.
4. Connect the power cable to the ceramic terminal (COM and 100V).
5. Connect the connection cable for the strobe light to the ceramic terminal (24V).
6. Put the terminal cover back on the rear of the speaker and slide the cover to the left. Tighten the screws again.
7. Fold the speaker's leaf springs upwards and insert the speaker into the ceiling cut-out until it is flush with the ceiling.

CE

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
:
:

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-11-19