DA-P 20-130/T BLACK-EN54

Sound projector for Voice Alarm, 20W power, certified EN 54-24



Mechanical Data

Colour	RAL 9005
Dimensions	138x204 mm
Weight (net)	1,44 kg
Power	20/10/5/2,5 W
Connector	2-pin ceramic block
Terminal Diameter	3,2 mm
Maximum Cable Passage	8 mm²
Mounting	Mounting bracket

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26

DA-P 20-130/T BLACK-EN54

4 260590 185778

Mounting Instruction

1. Mount the U-bracket on the ceiling with the appropriate screws for the surface.
2. If necessary, remove the speaker enclosure from the U-bracket.
3. Mount the cable junction box on the wall or ceiling with screws suitable for the surface.
4. Connect the loudspeaker cable to the terminals 100V and COM.
   If necessary, select a different power tapping.
5. Close the cover of the junction box.

Power Tappings

Black	Red	Yellow	Blue	Green
COM	20	10	5	2,5

CE
26

CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:020-14
ID-Code:SAA-LS20
1438-CPR-1094

TO MAKE PEOPLE LISTEN

Copyright ©2026 ic audio GmbH. All rights reserved. Date: 2026-10-26