

DA 10-260/T-EN54

Bi-directional sound projector for Voice Alarm, 10W power, certified EN 54-24



Technical Data

Colour	RAL 9010
Dimensions	201x176x160 mm
Dispersion -6dB, 500Hz	h/v 2x130°
Dispersion -6dB, 1KHz	h/v 2x150°
Dispersion -6dB, 2KHz	h/v 2x145°
Dispersion -6dB, 4KHz	h/v 2x75°
Sensitivity EN54-24, 1W/1m	89,6 dB
Sensitivity EN54-24, 1W/4m	77,0 dB
Frequency Range	237 - 12.400 Hz
Frequency Response	79 - 17.500 Hz
SPL IEC268-5, 1W/1m	89,0 dB
SPL EN54-24, Pmax/4m	86,0 dB
Power	10/6/3/1,5 W



DA 10-260/T-EN54

Mounting Instruction

1. Prepare the mounting holes for the mounting base on the wall or ceiling.
2. Insert the loudspeaker cable through the cable entry of the mounting plate / rear wall of the housing.
3. Connect the loudspeaker cable to the terminals 100V and COM.
If necessary, select a different power tapping.
4. Mount the mounting base on the previously prepared fixing holes with screws suitable for the surface.

Power Tappings

Black	Brown	Red	White	Green
COM	10	6	3	1,5



CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire
detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
D-68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:003-14
ID-Code:SAA-LS14
1438-CPR-1000