

DA-P 10-260/T-EN54

Bi-directional sound projector for Voice Alarm, 10W power, certified EN 54-24



Technical Data

Colour	RAL 9016
Dimensions	146x202 mm
Dispersion -6dB, 500Hz	h / v 2x130° / 2x130°
Dispersion -6dB, 1KHz	h / v 2x170° / 2x170°
Dispersion -6dB, 2KHz	h / v 2x160° / 2x160°
Dispersion -6dB, 4KHz	h / v 2x65° / 2x65°
Sensitivity EN54-24, 1W/1m	85,6 dB
Sensitivity EN54-24, 1W/4m	73,0 dB
Frequency Range	100 - 20.000 Hz
Frequency Response	90 - 25.000 Hz
SPL IEC268-5, 1W/1m	85,0 dB
SPL EN54-24, Pmax/4m	82,5 dB
Power	10/5/2,5 W



DA-P 10-260/T-EN54

Mounting Instruction

1. Mount the U-bracket on the ceiling with the appropriate screws for the surface.
2. If necessary, remove the speaker enclosure from the U-bracket.
3. Mount the cable junction box on the wall or ceiling with screws suitable for the surface.
4. Connect the loudspeaker cable to the terminals 100V and COM.
If necessary, select a different power tapping.
5. Close the cover of the junction box.

Power Tappings

Blue	Red	Yellow	Green
COM	10	5	2,5



CE-Symbol according to 93/68EWG
Measurements according to DIN IEC 268-5
RoHS compliant (2011/65/EU)
CPR compliance according 305/2011/EU

Loudspeaker for voice alarm systems for fire
detection and fire alarm systems for buildings
ic audio GmbH, Boehringerstraße 14A
D-68307 Mannheim, Germany

EN54-24:2008
Ref. Nr.:020-17
ID-Code:SAA-LS20
1438-CPR-1094